

2017 SPRING-SUMMER HIGHLIGHTED DRILL RESULTS
UTM Location

Zone	Drill				UTM Location					
	Hole	Dip	Azimuth	Easting	Northing		From (m)	To (m)	Interval (m)	Au g/t
DOUAY WEST	16-147	-55	4	704320	5491214	from	150.0	170.6	20.6	2.11
						incl.	151.4	153.0	1.6	5.25
						incl.	156.0	157.5	1.5	4.93
						incl.	159.0	160.5	1.5	5.58
						incl.	168.0	169.0	1.0	3.92
						and	221.8	225.0	3.2	0.56
	16-148	-45	357	704436	5491296	from	28.5	31.2	2.7	4.69
						incl.	30.0	31.2	1.2	9.61
						and	77.1	83.5	6.4	0.56
	16-149	-48	357	704449	5491175	from	90.0	113.1	23.1	2.2
						incl.	90.0	91.5	1.5	3.43
						incl.	106.5	108.0	1.5	9.65
						incl.	109.5	111.0	1.5	4.94
						incl.	111.0	112.0	1.0	4.08
						incl.	112.0	113.1	1.1	5.72
						and	219.0	223.5	4.5	1.05
	17-150	-50	357	704526	5491197	from	114.0	121.5	7.5	0.37
						and	204.0	240.0	36.0	0.89
						incl.	208.5	210.0	1.5	4.52
						incl.	214.5	216.0	1.5	3.09
						incl.	216.0	217.5	1.5	3.15
	17-151	-45	5	704623	5491328	from	70.5	75.0	4.5	3.53
						incl.	73.5	75.0	1.5	7.02
	17-152	-55	360	704598	5491122	from	89.0	93.5	4.5	0.41
						and	272.8	275.5	2.7	1.51
	17-153	-45	1	704714	5491102	from	93.0	97.5	4.5	0.66
						and	241.5	243.0	1.5	0.43
	17-190	-50	360	704800	5491160	from	87.0	94.5	7.5	1.39
						incl.	90.0	91.5	1.5	3.91
						and	174.0	177.0	3.0	0.65
MAIN PORPHYRY ZONES*	17-154			705800	5491345	from	199.5	204.0	4.5	0.27
						and	208.5	210.8	2.3	0.55
						and	225.0	228.0	3.0	1.26
	17-155			706375	5490910	from	36.0	39.0	3.0	1.7
						incl.	37.5	39.0	1.5	3.15
						and	55.5	87.0	31.5	0.59
						and	121.5	124.5	3.0	0.77
						and	132.0	136.5	4.5	0.82
	17-156			706500	5490890	from	54.0	58.5	4.5	0.53
						and	70.5	73.5	3.0	0.76
						and	85.0	87.0	2.0	0.34
						and	102.0	108.0	6.0	0.45
						and	121.5	133.5	12.0	1.26
						incl.	123.0	124.5	1.5	3.86
						and	141.0	144.0	3.0	1.41
						and	159.0	162.0	3.0	0.7
	17-157			706500	5490200	from	274.5	276.0	1.5	0.75
	17-158	-55	0	706650	5490655	from	88.4	89.6	1.2	3.03
						and	158.5	161.5	3.0	0.63
						and	227.3	250.5	23.2	0.83
						and	262.5	271.5	9.0	0.79
						and	279.0	286.5	7.5	0.99
						and	306.7	320.0	13.4	0.98
						incl.	314.2	315.5	1.3	4.04
						and	355.7	357.0	1.3	1.13

						and	387.4	406.4	19.0	1.05
						incl.	387.4	388.9	1.5	4.92
17-161	-75	360	706500	5490150	from	442.5	445.5	3.0	0.85	
17-182	-50	360	706700	5490300	from	375.0	382.5	7.5	1.03	
					and	405.0	408.0	3.0	0.63	
					and	436.5	442.5	6.0	0.55	
					and	447.0	448.5	1.5	0.55	
					and	471.0	472.5	1.5	0.58	
					and	478.5	481.5	3.0	0.43	
					and	562.5	567.0	4.5	0.41	
					and	577.5	579.0	1.5	0.31	
					and	595.5	609.0	13.5	0.46	
					and	634.5	649.5	15.0	0.47	
					and	661.5	673.5	12.0	0.3	
17-184			707000	5490290	from	35.2	39.7	4.5	0.36	
					and	63.7	68.2	4.5	0.29	
					and	159.8	161.3	1.5	0.33	
17-185			707000	5490150	from	70.2	72.9	2.7	0.28	
					and	402.9	411.8	8.9	0.47	
17-187	-55	360	706800	5490630	from	97.5	100.5	3.0	1.15	
					and	133.5	141.0	7.5	0.86	
					and	145.0	147.0	2.0	2.71	
					incl.	145.9	147.0	1.1	4.84	
					and	201.0	204.0	3.0	0.33	
					and	213.0	214.5	1.5	1.45	
					and	250.5	256.5	6.0	0.51	
					and	330.0	331.5	1.5	0.87	
					and	345.0	351.0	6.0	1.12	
					and	361.5	370.5	9.0	0.56	
					and	379.5	390.0	10.5	1.45	
					incl.	379.5	381.0	1.5	4.13	
					and	408.0	423.0	15.0	0.35	
					and	183.0	184.5	1.5	1.28	
					and	232.0	242.2	10.2	0.49	
17-192			706800	5490270	from	39.0	72.0	33.0	0.55	
					incl.	58.5	60.0	1.5	5.64	
					and	81.0	85.5	4.5	0.34	
					and	108.0	127.5	19.5	0.34	
					and	162.8	173.0	10.2	0.77	
					and	196.0	199.0	3.0	0.41	
17-194	-55	360	706050	5490640	from	364.5	370.5	6.0	1.28	
					and	381.5	396.3	14.8	1.37	
					incl.	390.0	391.5	1.5	5.52	
					and	402.7	403.7	1.0	0.64	
					and	426.4	427.9	1.5	1.08	
					and	516.0	517.5	1.5	1.47	
					and	537.0	538.5	1.5	0.74	
17-195	-50	360	706800	5490120	from	349.5	351.0	1.5	1.1	
					and	420.0	421.5	1.5	1.22	
17-196	-60	360	706800	5490500	from	102.3	103.5	1.2	0.59	
					and	143.0	144.3	1.3	0.95	
					and	171.0	172.5	1.5	0.91	
					and	204.0	207.0	3.0	0.65	
					and	499.5	505.5	6.0	0.33	
					and	517.5	531.0	13.5	0.38	
					and	544.0	554.5	10.5	0.47	
					and	562.0	565.5	2.7	0.54	
17-197A					and	80.4	104.3	23.9	0.51	

						and	114.3	115.3	1.0	0.81
						and	130.0	131.2	1.2	13.35
						and	143.4	144.1	0.7	0.87
						and	366.0	369.0	3.0	0.39
						and	456.2	457.5	1.3	0.78
						and	547.5	550.5	3.0	0.37
17-200	-50	360	707300	5491275	from	102.0	105.0	3.0	0.54	
					and	285.0	289.5	4.5	4.68	
					incl.	285.0	286.5	1.5	6.01	
					incl.	286.5	288.0	1.5	7.16	
					and	298.5	301.5	3.0	0.77	
					and	351.7	355.0	3.3	0.33	
17-202	-45	360	707450	5491168	from	64.5	66.0	1.5	0.6	
					and	255.0	264.0	9.0	4.53	
					incl.	255.0	256.5	1.5	15.7	
					incl.	258.0	259.5	1.5	6.86	
					and	336.0	336.8	0.8	1.07	
NW PORPHYRY	17-163	-50	353	705025	5491998	from	114.4	118.1	3.7	0.5
					and	193.0	197.5	4.5	0.59	
					and	200.5	206.5	6.0	0.38	
17-165	-50	356	705027	5491802	from	21.0	25.5	4.5	0.3	
					and	131.5	134.0	3.0	0.4	
					and	143.5	151.0	7.5	0.86	
					and	168.0	169.5	1.5	0.87	
					and	172.5	175.5	3.0	0.38	
					and	212.5	213.6	1.1	0.42	
					and	235.0	236.5	1.5	0.42	
					and	306.5	312.5	6.0	0.42	
17-167			705025	5491600	from	50.5	52.0	1.5	0.53	
					and	86.5	88.0	1.5	0.52	
					and	209.5	228.0	18.5	0.36	
					and	241.5	243.0	1.5	0.32	
					and	279.0	283.5	4.5	0.32	
17-168			703000	5492090	from	126.1	129.2	3.1	0.22	
					and	389.1	391.8	2.7	0.34	
17-169	-51	350	704800	5491700	from	204.0	238.5	34.5	0.79	
					and	312.0	316.5	4.5	2.46	
					incl.	312.0	313.5	1.5	5.32	
					and	325.5	328.5	3.0	0.44	
					and	336.0	345.0	9.0	0.72	
17-170	-50	360	704400	5491960	from	273.0	274.1	1.1	0.23	
17-171			705025	5491390	from	121.0	124.0	3.0	0.42	
					and	142.0	143.5	1.5	0.45	
17-172			704000	5492170	from	180.0	183.0	3.0	0.74	
					and	250.5	258.0	7.5	0.27	
					and	289.5	291.0	1.5	0.79	
					and	297.0	298.5	1.5	0.39	
17-173			705525	5492000	from	132.0	139.5	7.5	0.64	
					and	196.5	201.0	4.5	0.55	
					and	205.5	207.0	1.5	0.77	
					and	219.0	222.0	3.0	2.19	
					and	231.0	232.5	1.5	0.65	
17-174			703500	5491950	from	242.0	244.0	2.0	0.85	
					and	365.0	366.0	1.0	1.46	
17-175			705800	5492100	from	46.5	48.0	1.5	0.57	
17-178			703500	5491750	from	58.7	60.2	1.5	0.56	
					and	75.5	76.5	1.0	0.44	
					and	98.3	104.8	6.5	0.65	

	17-181			704000	5492420	from	49.0	50.0	1.0	1.93
					and	69.0	70.8	1.8	0.54	
					and	76.5	78.6	2.1	3.25	
					incl.	78.0	78.6	0.6	7.96	
					and	85.2	86.7	1.5	0.45	
					and	96.0	98.3	2.3	0.34	
					and	99.5	101.0	1.5	0.35	
					and	178.5	180.0	1.5	0.9	
	17-189			705525	5491700	from	142.5	149.6	7.1	0.46
					and	234.9	239.5	4.6	0.88	
					and	335.4	340.5	5.1	0.64	
	17-191			705800	5491700	from	63.8	64.9	1.1	0.59
					and	80.5	87.5	7.0	0.61	
	17-193			705525	5491600	from	94.5	99.0	4.5	0.5
					and	157.5	162.0	4.5	0.45	
					and	223.5	226.5	3.0	0.45	
					and	246.0	249.0	3.0	0.41	
					and	255.0	264.0	9.0	0.45	
					and	270.0	271.5	1.5	0.54	
CONDUCTOR "E"	17-176	-70	360	705854	5490173	from	129.0	130.5	1.5	1.81

Notes:

Footages shown are core lengths in metres (m). True widths represent an estimated 90% of core lengths.

Highlighted drill results above from press releases February 22, April 3, May 8 and July 17 (2017)

*Main Porphyry Zones: drilling includes drill-holes in the center segment of the porphyry system, which covers the (Porphyry Zone, 20 Zone, 10 Zone, Central Zone & the new North Zone)